



SMALL CAPACITY BUFFER TANKS FOR HEAT PUMP SYSTEMS

VB 1.2 3038 D02 P1

TIN Code	306162
Range	30
Net weight	12 kg
Insulation	34 mm
Heat losses ΔT 45K	32.1 W
Energy class	B
Maximum operational temperature	95 °C
Rated pressure of the water tank	6 bar
Diameter	386 mm



Thermo pocket	yes
Insulation	50 mm rigid PU
Number of inlets	2 number
Number of outlets	2 number



30 L SLIM | 2 inlets and 2 outlets | 1 pocket for thermo sensor

- INSUTECH technology that creates a HIGHLY-EFFICIENT INSULATION for preserving the temperature of the fluid
- METAL INLETS AND OUTLETS with a G1 ½" for a high flow rate:
- 2 INLETS and 2 OUTLETS
- 1 POCKET FOR THERMO SENSOR
- Option for HEATING ELEMENT INSTALLATION
- INTEGRATED MOUNTING PLATE for vertical wall installation
- AV opening
- Rated pressure 6 bar
- Option for ANTI-CONDENSATION INSULATION on the fittings
- Aesthetic white metal jacket

Serie information

VB 1.2 3038 D02 P1

Small capacity buffer tanks range includes models of 30 L Slim, 50 L Slim, 80 L and 100 L for vertical wall installation.

- NON-ENAMELED BUFFER TANKS
- FOR HEAT PUMP SYSTEMS
- INSUTECH technology that creates a HIGHLY-EFFICIENT INSULATION for preserving the temperature of the fluid
- METAL INLETS AND OTLETS with a G1 ½" for a high flow rate:
 - 4 INLETS and 4 OUTLETS for connection to TWO heat SOURCES - 50 L, 80 L and 100 L P2 models
 - 2 INLETS and 2 OUTLETS - 30 L, 50 L and 100 L P1 models
- POKETS FOR THERMO SENSORS:
 - 2 POKETS - 50 L, 80 L and 100 L P2 models
 - 1 POKET - 30 L, 50 L and 100 L P1 models
- Option for HEATING ELEMENT INSTALLATION
- INTEGRATED MOUNTING PLATE for vertical wall installation
- AV opening
- Rated pressure 6 bar



- Option for ANTI-CONDENSATION INSULATION on the fittings
- Aesthetic white metal jacket

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.