




Vaso autoclave con membrana intercambiabile per circuiti di acqua sanitaria.
Pressure tank with replaceable membrane for pressurized systems of sanitary water.
Réservoir sous pression à vessie remplaçable pour systèmes d'eau sanitaire.
Druckausdehnungsgefäß mit austauschbarer Membrane für Trinkwassersysteme.
Acumulador hidroneumático con membrana recambiable para circuitos de agua sanitaria.

Temperatura d'esercizio
Working temperature
Température d'exercice
Betriebstemperatur
Temperatura de trabajo

- 10° C
+ 100° C

Colore della verniciatura esterna
External finish color
Couleur de la peinture externe
Externe Beendenfarbe
Color pintura exterior

RAL 5015

Membrana in gomma
Rubber membrane
Vessie en gomme
Gummimembrane
Membrana en goma

EPDM

Controflangia zincata - Counter flange galvanized
Contre-bride galvanisé - Gegenflansch verzinkt - Contra brida galvanizada



Garanzia sul prodotto mesi: - Warranty months:
Garantie mois: - Monate Garantie: - Garantía meses:

24

Modello Model Modèle Model Modelo	Codice Code Code Code Código	Altezza Height Hauteur Höhe Altura H (mm)	Diametro Diameter Diamètre Durchmesser Diámetro Ø (mm)	Lunghezza Length Longeur Länge Longitud L (mm)	Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck Presión máxima de trabajo (bar)	Pressione di precarica standard Standard precharge pressure Pression de précharge standard Vordruck Presión de precarga estándar (bar)	Imballo Packing Emballage Verpackung Embalaje (mm)	Attacco Connection Raccordement Anschluss Conexión (inch)
VA018	AAGOE11B01CA1	305	280	430	10	1,5	(Pz1) 450X290X320	1 "
VA024	AAIOE11B01EA1	305	280	485	10	1,5	(Pz1) 510X290X320	1 "
VA035	AAJOE11B01EA1	376	365	440	10	1,5	(Pz1) 380X400X460	1 "
VA050	AAKOE11B01EA1	380	365	585	10	1,5	(Pz1) 380X400X590	1 "
VA060	AALOE11B01EA1	385	365	690	10	1,5	(Pz1) 380X400X700	1 "
VA080	AAMOE11B01EA1	430	410	725	10	1,5	(Pz1) 430X450X735	1 "
VA0100	AANOE11B11EA1	520	495	685	10	1,5	(Pz1) 510X540X700	1 "
VA0150	AAPOE11B11EA1	585	550	820	10	1,5	(Pz1) 570X610X850	1 "

Temperatura d'esercizio
Working temperature
Température d'exercice
Betriebstemperatur
Temperatura de trabajo

- 10° C
+ 100° C

Colore della verniciatura esterna
External finish color
Couleur de la peinture externe
Externe Beendenfarbe
Color pintura exterior

RAL 5015

Membrana in gomma
Rubber membrane
Vessie en gomme
Gummimembrane
Membrana en goma

EPDM

Controflangia verniciata - Painted counter flange
Contre-bride peinte - Lackierter Gegenflansch - Contra brida pintada



Garanzia sul prodotto mesi: - Warranty months:
Garantie mois: - Monate Garantie: - Garantía meses:

24

VA0200	AAQOG21B11FA1	628	600	920	10	2	(Pz1) 620X630X1030	1 1/4 "
VA0300	AASOG21B11FA1	680	650	1082	10	2	(Pz1) 680X700X1290	1 1/4 "

Controflangia inox AISI 304 disponibile su richiesta. - Stainless steel AISI 304 counter flange available on request.
Contre bride inox AISI 304 disponible sur requête. - Inox Flansch AISI 304 auf Anfrage.
Contra brida en acero inox AISI 304 bajo demanda.